

Data Sheet

# Proportional Valve Group PVG 16



The PVG 16 is a new member of the PVG family of valves. The PVG portfolio now comprises PVG 16, 32, 100 and 120 – providing flow up to 240 l/min.

A common feature is the modular build concept. This enables engineers to combine stacks of flexible slice-sections across the entire PVG family, making it possible to build up a valve group that meets precise requirements.

Furthermore, the compact external dimensions of the valve remain unchanged, no matter what combination is specified.

The PVG 16 is a hydraulic, load-sensing proportional valve, designed to give maximum flexibility in the design and build concept.

The PVG 16 is also designed as a load-sensing directional control valve, which helps improve application efficiency – reducing both cooling requirements and fuel expenses.

**Features**

- 40 mm [1.575 in] PVB module width
- PVB with BSP and UNF threads
- Compensated basic modules
- Uncompensated basic modules
- P-channel check valve
- Shock valves
- PVM with or w/o adjustment screws
- PVH, hydraulic actuation
- PVEO and PVEA
- Combination with PVG 32, 100 and 120

**Available spools**

- Closed or open neutral position
- Float
- Assymetrical flow options
- Electrical/mechanical or hydraulic actuation
- 5, 10, 25, 40 or 60 l/min  
[1.32, 2.64, 6.60, 10.57 or 15.85 US gal/min]

**Technical Data**
*Technical parameters*

<b>Maximum pressure</b>	Port P continuous	350 bar <sup>1)</sup>	[5075 psi]	
	Port P intermittent	400 bar	[5800 psi]	
	Port A/B continous	380 bar	[5510 psi]	
	Port A/B intermittent	420 bar	[6090 psi]	
	Port T, static/dynamic	25/40 bar	[365/580 psi]	
<b>Oil flow rated</b>	Port P	140/230 l/min	[37/61 US gal/min]	
	Port A/B	60 l/min	[16 US gal/min]	
<b>Spool travel</b>	Deadband	± 1.5 mm	[± 0.06 in]	
	Proportional range	± 5 mm	± 0.2 in]	
	Float position	± 7.5 mm	[± 0.3 in]	
<b>Maximum internal leakage at 100 bar [1450 psi] and 21 mm<sup>2</sup>/s [102 SUS]</b>	A/B → T without shock valve	20 cm <sup>3</sup> /min	[1.85 in <sup>3</sup> /min]	
	A/B → T with shock valve (system setting 30 bar [435 psi])	25 cm <sup>3</sup> /min	[2.15 in <sup>3</sup> /min]	
<b>Oil temperature (inlet temperature)</b>	Recommended temperature	30 → 60 °C	[86 → 140 °F]	
	Minimum temperature	-30 °C	[-22 °F]	
	Maximum temperature	90 °C	[194 °F]	
<b>Ambient temperature</b>		-30 → 60 °C	[-22 → 140 °F]	
<b>Oil viscosity</b>	Operating range	12 - 75 mm <sup>2</sup> /s	[65 - 347 SUS]	
	Minimum viscosity	4 mm <sup>2</sup> /s	[39 SUS]	
	Maximum viscosity	460 mm <sup>2</sup> /s	[2128 SUS]	
<b>Filtration</b>	Maximum contamination (ISO 4406)	23/19/16		
<b>PVM regulating range</b>	Proportional	13.9°		
	Float position	22.3°		
<b>PVM operating force</b>	PVM + PVMD	Neutral position	2.2 ± 0.2 N·m	[5.0 ± 1.8 lbf·in]
		Maximum stroke	2.8 ± 0.2 N·m	[6.3 ± 1.8 lbf·in]
	PVM + PVE <sup>2)</sup>	Neutral position	2.2 ± 0.2 N·m	[5.0 ± 1.8 lbf·in]
		Maximum stroke	2.8 ± 0.2 N·m	[6.3 ± 1.8 lbf·in]
	PVM + PVH	Neutral position	2.7 ± 0.2 N·m	[23.9 ± 1.8 lbf·in]
		Maximum stroke	7.1 ± 0.2 N·m	[62.8 ± 1.8 lbf·in]
<b>PVH pressure</b>	Regulating range	5 – 15 bar	[75 – 220 psi]	
	Maximum pilot pressure	30 bar	[435 psi]	
	Maximum pressure on T-port	10 bar	[145 psi]	
<b>PVE input voltage <sup>3)</sup></b>	Supply	11 – 32 V <sub>DC</sub>		
	Regulating range	25 – 75% of supply voltage		
<b>PVE SP pin output voltage <sup>3)</sup></b>	Float	0,5 V <sub>DC</sub>		
	Flow to B-port	1.25 – 2.5 V <sub>DC</sub>		
	Neutral	2.5 V <sub>DC</sub>		
	Flow to A-port	2.5 – 3.75 V <sub>DC</sub>		
	Error	5 V <sub>DC</sub>		

<sup>1)</sup> With PVS1 end plate. Using PVS end plate maximum 300 bar [4351 psi].

<sup>2)</sup> PVE without voltage.

<sup>3)</sup> Voltage is measured between spool output pin and ground (GND).

**Technical Literature**

[PVG 16 Technical Information, L1214235.](#)

[PVE-CI Technical Information, L1505234.](#)

**Danfoss Power Solutions (US) Company**  
2800 East 13th Street  
Ames, IA 50010, USA  
Phone: +1 515 239 6000

**Danfoss Power Solutions GmbH & Co. OHG**  
Krokamp 35  
D-24539 Neumünster, Germany  
Phone: +49 4321 871 0

**Danfoss Power Solutions ApS**  
Nordborgvej 81  
DK-6430 Nordborg, Denmark  
Phone: +45 7488 2222

**Danfoss Power Solutions Trading (Shanghai) Co., Ltd.**  
Building #22, No. 1000 Jin Hai Rd  
Jin Qiao, Pudong New District  
Shanghai, China 201206  
Phone: +86 21 3418 5200

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.